




Centra-Inochi Extreme Pit Shop Corporation

12 L. Fernandez St. Balintawak, Quezon City
 Phone/Fax: (632) 364 57 22; (632) 412 33 48
 www.inochi.com.ph
 sales@inochi.com.ph


INOCHI 12650 (12V 65Ah)



Specifications

Nominal Voltage		12V
Rated Capacity(20 hour rate)		65AH
Dimensions ± 1mm	Length	348mm(13.70")
	Width	168mm(6.61")
	Height	178mm(7.01")
	Total Height (with terminals)	
Weight		Approx.22kg (48.4lbs)
Standard Terminal		B2
Optional Terminal		A3

Discharge Characteristics(20°C,68°F)



Electrical Specifications

Capacity 77°F(25°C)	20 hour rate (3.2A)	65AH
	10 hour rate (6.05A)	60.5AH
	5 hour rate (11.06A)	55.3AH
	1 hour rate (37.1A)	37.1AH
Internal Resistance	Fully charged battery 77°F(25°C)	6.5m Ω
Capacity Affected by Temperature (20 hour rate)	104°F(40°C)	102%
	77°F(25°C)	100%
	32°F(0°C)	85%
	5°F(-15°C)	65%
Self-Discharge 77°F(25°C)	Capacity after 3 month storage	92%
	Capacity after 6 month storage	83%
	Capacity after 12 month storage	65%
Charge Constant Voltage	Cycle:Initial Charging Current less than19.5A Voltage14.4-15.0V77°F(25°C) Standby:Voltage13.5-13.8V77°F(25°C)	

Discharge Characteristics(0°C/32°F,40°C/104°F)

